

Magnecor 7mm ELECTROSPORTS 70 SS Ignition Lead Specifications

OVERALL LEAD ASSEMBLY

Outside Diameter of Cable.....	7mm.
Colour.....	Black.
Boot/Terminal Configuration.....	Various - to suit different domestic and foreign applications as well as customer special requirements.
Country of Manufacture.....	Cable: USA. Assemblies: USA, UK and Australia.

CABLE

Construction Type.....	Two section: Insulator bonded with tape to high tear strength, high heat resistant outer jacket.
Insulator Material.....	High dielectric silicone rubber.
Outer Jacket Material.....	Extreme high tear strength, high temperature resistant silicone rubber.
Heat Resistance.....	205° C (400° F) service temperature.
Dielectric Strength.....	45,000 volts.

CONDUCTOR

Conductor Size.....	1.90 mm in diameter.
Conductor Type.....	Magnecor Metallic Inductance RFI and EMI Suppressed. No conductive coatings applied.
Core.....	Ferrimagnetic base over Kevlar and fiberglass substrate.
Windings.....	77 turns per cm (200 turns per inch).
Windings Material.....	Stainless steel.
Resistance.....	98.4 ohm per cm, 3K ohm per ft. \pm 10%.
Capacity.....	45,000 volts, 2kVA.

TERMINALS

Spark Plug.....	Stainless steel snap-lock 180° bendable and fixed 90° styles.
Distributor and Coil.....	Brass, stainless steel snap-lock 180° and 90° styles.

PROTECTIVE BOOTS

Spark Plug.....	Silicone 205° C (400° F) - selection of straight, 45° and 90° styles used where applicable - special connector assemblies for some applications.
Distributor and Coil.....	EPDM or Silicone - some sets will be fitted with OE style connectors.

AVAILABILITY

NO MINIMUM ORDER REQUIRED

Available in sets to fit domestic and import car, truck, motorcycle and marine engines. Also, universal sets, individual leads, and tailored sets. Loose cable, boots and terminals can be purchased separately.

MAGNECOR®

ELECTROSPORTS 70 SS IGNITION CABLE

EXTREME STRENGTH
HIGH TEMPERATURE
RESISTANT SILICONE
RUBBER JACKET



METALLIC
INDUCTANCE
SUPPRESSED
CONDUCTOR
ACHIEVES
SUPERIOR EMI
SUPPRESSION
WITHOUT A
CONDUCTIVE
COATING

HIGH DIELECTRIC
STRENGTH INTERNAL
SILICONE INSULATOR
BONDED BY TAPE TO
OUTER JACKET FOR
SUPERIOR TERMINAL
RETENTION

NEW FOR 2006

Magnecor's (Original Equipment size)
7mm Lead Sets now use

ELECTROSPORTS 70 SS IGNITION CABLE

Vastly superior replacement for OE and aftermarket ignition leads (wires in USA) using carbon conductors or resistor/connectors at lead ends, all of which reduce spark energy when deterioration develops with usage.

ELECTROSPORTS 70 SS IGNITION CABLE, with its updated high-tech wire-wound conductor, will properly suppress both RFI and EMI on all engines without reducing spark current or deteriorating with use. The high tear strength silicone rubber insulating jacket provides better insulation than most 8mm aftermarket ignition leads, and new construction provides better terminal retention than ever before.

Any lead set using **ELECTROSPORTS 70 SS IGNITION CABLE** can be used on both older and newer carburetted engines as well as the most modern fuel injected engines using any electronic engine management system. Suppression is also provided for 2-way radio and computer equipment.

www.magnecor.com

TECHNICAL INFORMATION

MAGNECOR[®] ELECTROSPORTS 70 IGNITION CABLE

For over 20 years Magnecor manufactured ignition leads using its 7mm **HIGH PERFORMANCE IGNITION CABLE**. Lead sets (wire sets in USA) using this cable were very popular as a superior replacement for 7mm size original equipment and aftermarket ignition leads using limited-life carbon conductors and resistor/connectors at lead ends. Over the years, the wire-wound conductor was updated to provide better RFI suppression, and later versions achieved moderate EMI suppression.

A small 7mm insulating jacket makes providing a wire-wound conductor to properly suppress EMI (needed by late model engines) both difficult and expensive. To suppress EMI, most manufacturers use leads with carbon conductors and resistor/connectors at lead ends. Although these leads deteriorate with use and spark current is reduced, manufacturers are not concerned, because they all treat ignition leads as service items to be replaced regularly. Others in the aftermarket use cheap wire-wound conductors that cannot properly suppress EMI (no mention is ever made of this fact).

In the past, it has been a policy at Magnecor to recommend our 8.5mm **KV85 COMPETITION CABLE** sets (designed primarily for race engines) if we thought a possible EMI problem could arise on later model engines fitted with 7mm leads as original equipment. Of course, not all vehicle owners necessarily want to purchase more expensive larger diameter ignition leads designed for a race engine. All they want is good ignition leads with a conductor providing proper suppression that won't deteriorate with usage – more so, with so many late model “multi-valve” engines using ignition leads (fitted with complicated extended spark plug connectors) that have become very expensive and time consuming to replace.

The good news is, with the recent introduction of our **ELECTROSPORTS 70 IGNITION CABLE**, we can now offer a 7mm ignition cable with a wire-wound conductor to properly suppress both RFI and EMI.

Lead sets using **ELECTROSPORTS 70 IGNITION CABLE** can be used on both older and newer carburetted engines and the most modern fuel injected engines using any electronic engine management system. Excellent suppression is also provided for 2-way radio equipment. In addition, a new insulating jacket provides better insulation than most 8mm original equipment and aftermarket leads, and new construction provides better terminal retention than ever before.

Remaining Limitation

When used with either the original ignition system or a better ignition system designed for street use, lead sets using our **ELECTROSPORTS 70 IGNITION CABLE** will prove to be vastly superior to all limited-life 7mm original equipment and aftermarket carbon conductor leads, resistor/connector leads and other brand wire-wound conductor leads. However, **no** 7mm or 8mm cable size leads can fully insulate the maximum output from a racing ignition system. If you intend to ever modify your vehicle for competition we recommend our lead sets using either our:

KV85 COMPETITION CABLE (8.5mm)
or
R-100 RACING CABLE (10mm)

For more information about Magnecor products, visit our web site: www.magnecor.com